Blackline SI2⁺


Compact, sub-bass system

features

- Very compact sub-bass system
- ▶ Long excursion 12" (300mm) driver
- Active/passive operation
- ▶ Top hat fitting for pole mounting F8⁺/F10⁺
- Five year limited warranty


applications

- Club sound reinforcement
- Theatre sub-bass
- AV presentations



The \$12⁺ is provided with a top hat fitting that can be used to pole mount an F8⁺ or F10⁺ above the enclosure.

overall dimensions





technical specifications

TYPE	Compact, sub-bass system
FREQUENCY RESPONSE (I)	$52Hz-150Hz \pm 3dB$
	-10dB @ 43Hz
DRIVERS	12" (300mm)/3" (75mm) voice coil LF driver
RATED POWER (2)	400W AES, 1600W peak
RECOMMENDED AMPLIFIER	400W-1200W into 4 ohms
SENSITIVITY (3)	100dB (half space)
MAXIMUM SPL (4)	126dB continuous, 132dB peak (half space)
NOMINAL IMPEDANCE	8 ohms
DISPERSION (-6dB)	
CROSSOVER	120Hz active/passive low pass filter
ENCLOSURE	55 litre, multi-laminate birch ply
FINISH	Textured black paint
PROTECTIVE GRILLE	Black perforated steel
CONNECTORS	2 x Neutrik NL4
PIN CONNECTIONS	LF+,-: I+,I-, Link thro': 2+,2-
FITTINGS	I x mounting pole socket
	2 x pocket handles
DIMENSIONS	(W) 398mm x (H) 571mm x (D) 364mm
	(W) 15.6ins x (H) 22.5ins x (D) 14.3ins
WEIGHT	20kg (44lbs)

Century Point, Halifax Road, Cressex Business Park,
High Wycombe, Buckinghamshire HP12 3SL, England.
Telephone: +44 (0)1494 533312 Facsimile: +44 (0)1494 438669
E-mail: info@martin-audio.com
All information is Copyright © 2007 Martin Audio Ltd.

